


K.A.R.L.® Climate Risk and Vulnerability Analysis

Assessment of physical risks within the framework of the environmental objective 2 “Adaptation to climate change” from the EU Taxonomy Regulation (2020/852).



Site information

Address: Christ the Redeemer. Brazil

Latitude: -22,951749

Longitude: -43,210467

Elevation (m a.s.l.): 462,00

Object type

K.A.R.L.[®]-vulnerability:

IMCL03

Simplified vulnerability:

Immobilie

Order information

Date of the analysis: 12.09.2025

Customer: landmark

Taxonomy-Version: 1.2.0.1

Overview of climate risk assessment

Location data: Christ the Redeemer. Brazil (-22,951749 / -43,210467)

Object type: Immobilie (IMCL03)

	Climate-related hazards (EU Taxonomy 2020/852)	Current* risk	Future** worst-case risk	Chapter
Temperature	Changing temperature (<i>chronic</i>)	● low	● low	1.1
	Heat stress (<i>chronic</i>)	● medium	● medium	1.2
	Temperature variability (<i>chronic</i>)	● not relevant	● not relevant	1.3
	Permafrost thawing (<i>chronic</i>)	- / -	- / -	1.4
	Heat wave (<i>acute</i>)	● medium	● medium	1.5
	Cold wave/frost (<i>acute</i>)	● not relevant	● not relevant	1.6
	Wildfire (<i>acute</i>)	● low	● low	1.7
Wind	Changing wind patterns (<i>chronic</i>)	● not relevant	● not relevant	2.1
	Cyclone, hurricane, typhoon (<i>acute</i>)	● medium	● medium	2.2
	Storm (including snow-, dust- and sandstorms) (<i>acute</i>)	● medium	● medium	2.3
	Tornado (<i>acute</i>)	● low	● low	2.4
Water	Changing precipitation patterns and types (rain, hail, snow/ice) (<i>chronic</i>)	● low	● low	3.1
	Precipitation or hydrological variability (<i>chronic</i>)	● not relevant	● not relevant	3.2
	Ocean acidification (<i>chronic</i>)	- / -	- / -	3.3
	Saline intrusion (<i>chronic</i>)	● low	● low	3.4
	Sea level rise (<i>chronic</i>)	● not relevant	● not relevant	3.5
	Water stress (<i>chronic</i>)	● not relevant	● not relevant	3.6
	Drought (<i>acute</i>)	● not relevant	● low	3.7
	Heavy precipitation (rain, hail, snow/ice) (<i>acute</i>)	● medium	● medium	3.8
	Flood (coastal, fluvial, pluvial, groundwater) (<i>acute</i>)	● not relevant	● not relevant	3.9
	Glacial lake outburst (<i>acute</i>)	- / -	- / -	3.10
Solid mass	Coastal erosion (<i>chronic</i>)	- / -	- / -	4.1
	Soil degradation (<i>chronic</i>)	● not relevant	● low	4.2
	Soil erosion (<i>chronic</i>)	● not relevant	● low	4.2
	Solifluction (<i>chronic</i>)	- / -	- / -	4.3
	Avalanche (<i>acute</i>)	● not relevant	● not relevant	4.4
	Landslide (<i>acute</i>)	● low	● medium	4.5
	Subsidence (<i>acute</i>)	● low	● low	4.6

*The current risk refers to the hazard of the near past (1985 to 2014) and depends on the sensitivity of the object under investigation. **The "worst case" risk is the highest risk across all scenarios and time periods.

Notes on the evaluation

This document presents the results of a climate risk and vulnerability analysis conducted by KA Köln.Assekuranz Agentur GmbH for a chosen object. The present analysis fulfils all requirements from the EU-Taxonomy Regulation for a robust climate risk analysis, which are required for the environmental objective 2 “climate change adaptation”.


As a part of the present analysis 28, both chronic and acute natural hazards were analysed on a site-specific basis. The aim is to identify all significant risks for the object under investigation, both under current and future climate conditions. For this the hazards were analysed not only on basis of observational data but also using an ensemble of 20 climate models, considering the prescribed emission scenarios (SSPSSP1-2.6, SSP2-4.5, SSP5-8.5) for four time periods (around 2000, 2030, 2050, 2085).

Emission scenarios

Three emission scenarios are considered separately in the analyses, two extreme scenarios (SSP1-2.6, SSP5-8.5) and one intermediate scenario (SSP2-4.5), in order to cover the entire range of currently conceivable trends.

SSP1-2.6 is the scenario with the smallest increase in emissions from 2020 onwards. In this scenario, the associated temperature increase compared to pre-industrial times remains below 2 °C, which can only be achieved through far-reaching, globally effective climate protection measures.

SSP5-8.5 describes the strongest increase in emissions. In this scenario, temperature increases of around 5 °C are expected by the end of the 21st century.



Global temperature increase compared to pre-industrial times.

Schematic illustration.

Fundamentals of risk assessment

As a result, an assessment of the location- and object-related risk is provided for each natural hazard. The risk is determined on one hand by the hazard at the location due to the specific natural hazard (hazard analysis) and on the other hand by the associated potential damages to the object under investigation (vulnerability).

Acute vs. chronic natural hazards To calculate the risk, it is important to distinguish between chronic and acute hazards: acute natural hazards are sudden and short-term events such as storms or floods with immediate, often devastating effects on people, property, and the environment. Chronic natural hazards, on the other hand, develop over a longer period, such as the slowly rising sea level or long-lasting droughts, which have continuous impacts on certain regions or ecosystems.

Hazard analysis The first step in risk assessment involves analysing relevant data sets to assess the local hazard situation of the respective natural hazard. For acute hazards, it must be clarified how often a location can be affected by an event, such as a flood or a storm of a certain intensity. For chronic natural hazards, it is more about assessing the general situation, e.g., how water availability or sea levels at a location will change in the long term. The data basis used for the hazard analysis is provided in the report in addition to the risk assessment.

Vulnerability Vulnerability is used to describe how sensitively an object under investigation reacts to a natural event of a certain intensity. For example, certain temperature-related natural hazards often have no relevant impact on the building structure, whereas these issues can be very crucial for agriculture. While hail damage to solid new buildings is often negligible, especially when measured against the value of the property, hail damage to cars can quickly lead to a total loss.

Risk classification A pre-defined vulnerability was selected for the present analysis. This is the only way to estimate the extent of damage to the property that can be expected in the long term with respect to the identified hazard situation. The resulting long-term damage value corresponds to the risk. Moreover, for some natural hazards, additional site factors (such as protective measures or special exposure of the site) are taken into account in the risk assessment, which can influence the local risk situation.

The determined risk values are issued according to a four-stage, qualitative classification system (traffic light colours). The table below describes what each risk category signifies regarding potential damages and the development of adaptation measures.

Risk classification	Damage	Adaption measures
- / -	The occurrence of the natural hazard at the site or an adverse effect on the object under investigation can be ruled out .	Adaptation measures are not necessary.
● not relevant	Potential damage is negligible .	Adaption measures are not necessary.
● low	Potential damage is low . No substance damage.	In individual cases, an inspection of the site is advisable. Adaptation measures may be useful in exceptional cases.
● medium	Damage of a medium extent is possible or substance damage cannot be ruled out in extreme cases.	An on-site examination of the situation is strongly recommended. Adaptation measures must be decided on a case-by-case basis.
● high	A significant risk has been identified. Substance damage is possible.	Effective adaptation measures are required to reduce the risk (taxonomy compliance).

All significant risks are identified using appropriate, officially recognized and global data and methods, which are described in detail to users in a separate manual.

The K.A.R.L. Climate and Vulnerability Analysis presented here was automatically generated and has not been reviewed by experts of the KA Köln.Assekuranz Agentur GmbH. If you have any questions about the results or see further explanations, we offer consultation with our experts at favourable terms.

Team K.A.R.L. (team.karl@koeln-assekuranz.com)

Detailed description of the perils

1 Temperature-related risks

1.1 Changing temperature (chronic)

The present analysis addresses the effects resulting from a slow and continuous change in the annual mean temperature. Extreme events are not considered in this analysis. The risk assessment is based on the annual mean temperature and its adverse effects on the object under investigation (vulnerability).

Note: Only the change in air temperature is analyzed. Changes in water temperatures are usually not relevant for the objects under investigation.

Current conditions In the reference period (1985-2014), the annual mean temperature at the site is **23.90 °C**. During this period, the annual mean temperature has increased by **0.015 °C** every year.

Based on the selected vulnerability, **a low adverse effect** on the object under investigation is to be expected from the mean annual temperature. This results in **a low risk**.

Climate outlook Table 2 lists possible future changes in the annual mean temperature, which were calculated based on an ensemble of 20 climate models for the site under investigation. A maximum change in annual mean temperature is projected for scenario **SSP5-8.5** and time period **2070-2099** with **an increase of +3.29 °C** compared to the reference period.

For the maximum projected annual mean temperature, **a low adverse effect** on the object under investigation is to be expected based on the selected vulnerability. This results in **a low risk**.

		Changes compared to 1985-2014			
	Reference 1985-2014	Scenario	short-term 2015-2044	medium-term 2035-2064	long-term 2070-2099
Annual mean temperature °C	23.90	SSP1-2.6	+0.54	+0.91	+0.99
		SSP2-4.5	+0.61	+1.10	+1.70
		SSP5-8.5	+0.73	+1.54	+3.29

Table 2: Projected changes in annual mean temperature for three 30-year periods and scenarios determined based on the model ensemble (CMIP6). The values of the reference period were derived from the ERA5 reanalysis data.

General impacts Changes in the annual mean temperature primarily affect agriculture, forestry, and fisheries. They also influence other ecosystem-related activities, such as ecosystem restoration, tourism, and water used for cooling. Rising temperatures can additionally lead to health problems, as disease vectors (i.e., tiger mosquitoes, ticks, etc.) increase or allergy seasons lengthen.

1.2 Heat stress (chronic)

Heat stress is defined as the exposure of humans and the environment to persistently high temperatures. The risk assessment is based on a heat stress index developed by KA and the associated adverse effects on the object under investigation (vulnerability).

The heat stress index primarily relates to the duration of heat waves, which pose a particular threat due to persistently high temperatures both during day and night. Index values range from 0 to 10, with 0 representing no heat stress and 10 representing extremely stressful and frequently recurring situations with high temperatures.

Current conditions With a current heat stress index of **8.50**, the site under investigation is located in an area with **a strong exposure** of heat stress.

Based on the selected vulnerability, **a medium adverse effect** on the object under investigation is to be expected from heat stress. This results in **a medium risk**.

Climate outlook Table 3 lists possible future heat stress indices, which were calculated based on an ensemble of 20 climate models for the site under investigation. A maximum heat stress of **10** is projected for scenario **SSP5-8.5** and time period **2070-2099**. This corresponds to **a very strong exposure**.

For the maximum projected heat stress, **a medium adverse effect** on the object under investigation is to be expected based on the selected vulnerability. This results in **a medium risk**.

		Projected heat stress-indices			
	Reference	Scenario	short-term	medium-term	long-term
	1985-2014		2015-2044	2035-2064	2070-2099
Heat stress-indices	8.50	SSP1-2.6	8.80	9.10	9.20
		SSP2-4.5	8.90	9.20	9.80
		SSP5-8.5	9.00	9.60	10.00

Table 3: Projected heat stress indices for three 30-year periods and scenarios determined based on the model ensemble (CMIP6). The values represent sums from the values of the reference period (ERA5) and the mean anomalies of the model ensemble. The values of the reference period were derived from the ERA5 reanalysis data.

General impacts Heat stress can impair physical and mental performance, especially in non-air-conditioned rooms or when working outdoors. Heat can also damage materials (e.g., by deformation), leading to the deterioration of means of production and infrastructure. Furthermore, an elevated heat stress can pose serious risks to human health ranging from a reduction of the workforce productivity to heat-related fatalities. The effects of heat stress are likely to increase in urban areas.

1.3 Temperature variability (chronic)

Temperature variability is the fluctuation in temperatures over the course of the day or year. This is a chronic hazard which results from a slow change in the climatic mean.

The risk assessment is based on the average difference between the daily maximum and minimum temperature and its impact on the object under investigation (vulnerability).

Current conditions In the reference period (1985-2014), the mean daily temperature difference at the site is **5.76 °C**.

Based on the selected vulnerability, **no adverse effect** on the object under investigation is to be expected from the daily temperature difference. This results in **no relevant risk**.

Climate outlook Table 4 lists possible future changes in daily temperature differences, which were calculated based on an ensemble of 20 climate models for the site under investigation. A maximum change in the daily temperature difference is projected for scenario **SSP5-8.5** and time period **2035-2064** with an increase of **+0.21 °C** compared to the reference period.

For the maximum projected fluctuation in the daily mean temperature, **no adverse effect** on the object under investigation is to be expected based on the selected vulnerability. This results in **no relevant risk**.

		Changes compared to 1985-2014			
	Reference	Scenario	short-term	medium-term	long-term
	1985-2014		2015-2044	2035-2064	2070-2099
Daily mean temperature difference °C		SSP1-2.6	+0.02	+0.12	-0.04
	5.76	SSP2-4.5	-0.06	-0.14	0.00
		SSP5-8.5	-0.13	+0.21	+0.09

Table 4: Projected changes in the daily mean temperature difference for three 30-year periods and scenarios determined based on the model ensemble (CMIP6). The values of the reference period were derived from the ERA5 reanalysis data.

General impacts Changes in temperature variability have similar effects as the mean temperature increase (see 1.1), i.e., agriculture, forestry and fisheries are primarily affected. Extreme temperature differences, especially during the day, can have a negative impact on building materials or infrastructure, such as roads or rails. The adverse effect on buildings is rather low. However, in regions with high daily and seasonal temperature fluctuations, materials (e.g., cladding, window frames, seals) are subjected to greater stress and can therefore become more susceptible to e.g., hail damage (skylights).

The increase in average temperatures is often accompanied by temperature extremes and an increase in the temperature variability. That is to say, in regions with a strong increase in average temperatures, the temperature variability will also increase (e.g., in the Mediterranean region in Europe).

1.4 Permafrost thawing (chronic)

Permafrost are permanently frozen soils that occur in polar regions and mountains. The soils must be permanently frozen for at least two consecutive years. However, the surfaces of permafrost soils can thaw to a depth of about half a meter during summer.

The present analysis uses permafrost simulations to assess the hazard. These give the extent of permafrost in percentage for the past climate (1960- 1990) and for different warming scenarios (from +1 °C to +6 °C).

These warming scenarios include all temperature increases modeled in the typically used emission scenarios.

Current and future conditions Due to its location, it can be **excluded** that the site under investigation is located in a permafrost region. Since all considered emission scenarios lead to an increase in global temperatures in the coming decades, it can also be **excluded** that permafrost will be present at the site in the future.

General impacts Thawing permafrost can impact the local landscape, infrastructure, economy, and population. The melting of irregularly distributed ice can lead to uneven subsidence of the land surface, which can cause roads, railways, runways, buildings, and oil and gas pipelines to subside, among other things. Permafrost thawing can affect the global climate and the entire ecosystem through feedback effects by releasing more greenhouse gases which consequently accelerate global warming.

1.5 Heat wave (acute)

A heat wave is a period of unusual hot weather that is particularly stressful for people and the environment. In the present analysis, a heat wave refers to a period of at least three consecutive days with a maximum daytime temperature greater than 30 °C ("Hot Days") and nighttime temperatures above 20 °C ("Tropical Nights"). The risk is assessed based on the average number of heat wave days per year at the site and their adverse effects on the object of investigation (vulnerability).

Note: *In many regions, including Central Europe, very low values (< 1) are calculated for the referenced period, which seem to contradict the definition of a heat wave as well as the personal experience. Several factors are responsible for this: The averaging required for the climate statement is of major importance. For example: a heat wave with a value of 0.5 corresponds to a total of 15 heat wave days within the 30-year reference period. Years without heat waves (in terms of the definition!!) are included in the averaging with a value of 0. The reference period (1985 – 2014) was not yet so strongly influenced by climate change, therefore the probability of heat waves was lower. Local temperature phenomena (e.g., urban heat islands, which are also governed by urban planning) cannot be adequately captured by the climate models, which can lead to small local deviations from the observations.*

Current conditions During the reference period (1985-2014), an annual average of **180.00 heat days** were recorded at the site under investigation which were part of a heat wave.

Based on the selected vulnerability, **a medium adverse effect** on the object under investigation is to be expected from heat waves. This results in **a medium risk**.

Climate outlook Table 5 lists possible future changes in heat wave days, which were calculated based on an ensemble of 20 climate models at the site under investigation. A maximum change is projected for scenario **SSP5-8.5** and time period **2070-2099** with **an increase of +67.2** heat wave days in average compared to the reference period.

For the maximum projected heat wave days, **a medium adverse effect** on the object under investigation is to be expected based on the selected vulnerability. This results in **a medium risk**.

			Changes compared to 1985-2014		
			Reference	Scenario	
			1985-2014	2015-2044	2035-2064
				2070-2099	
Heat wave days <i>Days per year</i>		SSP1-2.6	+5.40	+10.90	+12.60
	180.00	SSP2-4.5	+9.00	+16.50	+26.00
		SSP5-8.5	+10.50	+26.10	+67.20

Table 5: Projected changes in heat wave days for three 30-year periods and scenarios determined based on the model ensemble (CMIP6). The reference period values were derived from the ERA5 reanalysis data.

General impacts Heat waves primarily impair physical and mental performance as well as the well-being, especially in non-air-conditioned rooms or when working outdoors. In addition, heat waves can lead to a deterioration in air quality. Heat can also damage materials (e.g., by deformation), leading to the deterioration of means of production and infrastructure.

1.6 Cold wave/ frost (acute)

A cold wave is a period of unusual cold weather. In the present analysis, the risk from cold waves is assessed based on the number of annual frost days (daily minimum temperature < 0 °C) and their adverse effects on the object under investigation.

Current conditions During the reference period (1985-2014), an annual average of **0.00 frost days** were recorded at the site.

Based on the selected vulnerability, **no adverse effect** on the object under investigation is to be expected from cold waves. This results in **no relevant risk**.

Climate outlook Table 6 lists potential future changes in annual frost days, which were calculated based on an ensemble of 20 climate models at the site under investigation. A maximum change is projected for scenario **SSP1-2.6** and time period **2015-2044** with **an increase of 0** frost days in average compared to the reference period.

For the maximum projected frost days, **no adverse effect** on the object under investigation is to be expected based on the selected vulnerability. This results in **no relevant risk**.

			Changes compared to 1985-2014				
			Reference	Scenario	short-term	medium-term	long-term
			1985-2014		2015-2044	2035-2064	2070-2099
Frost days <i>Days per year</i>				SSP1-2.6	0.00	0.00	0.00
		0.00		SSP2-4.5	0.00	0.00	0.00
				SSP5-8.5	0.00	0.00	0.00

Table 6: Projected changes in annual frost days for three 30-year periods and scenarios determined based on the model ensemble (CMIP6). The values of the reference period were derived from the ERA5 reanalysis data.

General impacts Extreme cold temperatures can have negative effects on materials and production processes as well as on human health. Late frost poses a risk for fruit-growing, especially at the time of fruit blossom. In regions with prevailing cold climates, it is assumed that buildings are adapted to the cold temperatures. Therefore, the impact of low temperatures is generally low. A decrease in cold snaps has already been observed in Europe and is expected to intensify as climate change progresses. In contrast, the risk of late frosts has increased in Europe in recent years.

1.7 Wildfire (acute)

Forest- and wildland fires (referred as wildfire hereafter) are fires that occur in forests, grasslands, and agricultural land. They are initiated intentionally, accidentally or by natural causes after a prolonged dry period. The risk for the occurrence of a wildfire depends on the climatological conditions on site and on the amount of combustible vegetation in the immediate vicinity of the site. Therefore, this risk analysis is based on two variables that describe these conditions:

1. The **wildfire potential** is calculated from various, predominantly climatological parameters (relative humidity, drought stress, prevailing wind speed, etc.) that can influence the occurrence of wildfires. Therefore, the probability that a wildfire occurs and their intensity (e.g., duration, spatial extent) increases with the potential. The wildfire potential is given as a unitless index number with values between 0 and 10, where 10 refers to an extremely high wildfire potential due to the prevailing climatological conditions.
2. The four-level **combustibility index** derived from the land use data indicates whether and how much combustible vegetation (e.g., the combustibility is high for closed forests and low for grasslands) is present in the vicinity of the site.

The resulting risk is highest when climatological conditions favor the emergence of wildfires and at the same time sufficient combustible materials exist in the surrounding.

Current conditions Based on the prevailing climatological conditions at the site during the reference period (1985-2014), the wildfire potential is **low (3.2)**.

According to the land use data, **a low proportion** of vegetation can be assumed at the site under investigation. This results in **a low risk** based on the selected vulnerability.

Note: *Due to potential inaccuracies in the land use data, it is strongly recommended that vegetation in the immediate vicinity of the site is examined.*

Climate outlook Table 7 lists possible future wildfire potentials, which were calculated based on various climate simulations. The maximum wildfire potential is **medium (4.1)** and is projected for scenario **SSP1-2.6** and time period **2035-2064**.

Note: *Since predictions or possible future projections about the development of vegetation conditions are currently not available, the risk assessment is based on current land use data.*

Based on the selected vulnerability and assumption that the proportion of combustible vegetation components does not change, there will be at most **a low risk** in the future.

		Projected wildfire potential			
	Reference 1985-2014	Scenario	short-term 2015-2044	medium-term 2035-2064	long-term 2070-2099
Wildfire potential	3.2	SSP1-2.6	3.5	4.1	4.1
		SSP2-4.5	4.1	3.5	3.5
		SSP5-8.5	3.8	3.8	4.1

Table 7: Projected future wildfire potentials for three 30-year periods and scenarios determined based on the model ensemble (CMIP6). The values of the reference period were derived from the ERA5 reanalysis data.

General impacts Wildfires pose a significant hazard to social, economic, or ecological values. Fires can not only completely destroy properties, but also release pollutants (e.g., particulate matter and

dioxins) that pose a threat to human health. Increasing periods of heat and drought due to climate change contribute to the expansion of fire-prone areas and the extension of the wildfire season. Wildfires exacerbate global warming through the release of greenhouse gases.

2 Wind-related risks

2.1 Changing wind patterns (chronic)

Changing wind patterns describe slow and chronic changes in the mean wind speeds, while extreme events are not considered. The risk assessment is based on modeled trends in mean wind speeds at 10 m above the ground surface and their adverse effects on the object under investigation (vulnerability).

Current conditions In the reference period (1985-2014), the **mean wind speed** at the site is **12.75 km/h**.

Based on selected vulnerability, **no adverse effect** on the object under investigation is to be expected. This results in **no relevant risk**.

Climate outlook Table 8 lists possible future changes in mean wind speeds, which were calculated based on an ensemble of 20 climate models for the site under investigation. A maximum change in mean wind speed is projected for scenario **SSP5-8.5** and time period **2070-2099** with an **increase of +1.8 km/h** compared to the reference period.

For the maximum projected change in mean wind speed, **no adverse effect** on the object under investigation is to be expected based on the selected vulnerability. This results in **no relevant risk**.

	Reference 1985-2014	Scenario	Changes compared to 1985-2014		
			short-term 2015-2044	medium-term 2035-2064	long-term 2070-2099
Mean wind speed <i>km/h</i>	12.75	SSP1-2.6	+0.40	+0.25	+0.04
		SSP2-4.5	+0.43	+0.47	+0.79
		SSP5-8.5	+1.66	+1.55	+1.80

Table 8: Projected changes in mean wind speed for three 30-year periods and scenarios determined based on the model ensemble (CMIP6). The values of the reference period were derived from the ERA5 reanalysis data.

General impacts Changing mean wind speeds primarily affect the wind energy sector as well as the industries and populations that depend on it. In addition, changes in wind patterns (sometimes in combination with other climatological phenomena, such as drought) also affect several other sectors. Stronger winds, for example, can exacerbate drought and intensify the wildfire season. Weaker winds can increase air pollution in cities. Wind also plays an important role in nature, as it e.g., influences the growth, reproduction, and distribution of plants.

2.2 Cyclone, hurricane, typhoon (acute)

Cyclones (Northern Indian Ocean), hurricanes (Atlantic Ocean), and typhoons (Pacific Ocean) are tropical storms that occur in different regions of the world. All tropical storms form over tropical waters (usually between 20° N and 20° S) with a sea surface temperature of at least 26 °C as a violent low-pressure vortex that can reach diameters of 1,000 km. Tropical storms can cause enormous damage due to high wind speeds, storm surges and intense precipitation.

Current conditions The site under investigation is located in an area, where hurricanes can occur. The storm analysis (chapter 2.3) includes the possible risk of hurricanes.

Climate outlook Whether and how the spatial extent of tropical cyclone areas may change in the future is not considered in the present analysis. The possible future risks from tropical cyclones are part of the storm analysis in the following chapter.

General impacts Tropical cyclones can cause catastrophic destruction over large areas due to high wind speeds, landslides, and flooding. This, among other things, can lead to severe damage to residential buildings in an entire region. Tropical cyclones can endanger shipping at sea due to storms and high swells. If wind-induced waves run up onto the coastline, they can cause flooding and erosion.

2.3 Storm (acute)

Storms are defined as strong wind events with wind speeds of at least 75 km/h, since the first damage can usually occur from this wind speed. The analysis of the storm risk is carried out with the natural hazard model K.A.R.L.. The calculations for the reference period are based on the evaluation of wind data from many weather stations worldwide. Future trends are estimated by using an ensemble of 20 climate models.

K.A.R.L. does not distinguish between tropical and extratropical storms. Additionally, the digital elevation model is used to capture local wind effects.

The calculated risk in percent per year (% p.a.) by K.A.R.L. corresponds to the expected mean annual loss. This is the loss that occurs on a long-term statistical average per year due to the natural hazard under consideration.

Current conditions The storm risk (in relation to the year 2025) calculated by K.A.R.L. based on the selected vulnerability is **0.1163 % p.a.** This results in **a medium risk** for the object under investigation.

Climate outlook Table 9 lists potential future storm risks (% p.a.), which were calculated using the K.A.R.L. model based on the selected vulnerability and an ensemble of 20 climate models for the site under investigation.

The maximum projected storm risk is **0.1549 % p.a.** and was simulated for the time period **2015-2044** and scenario **SSP5-8.5**. This results in **a medium risk** in the future for the object under investigation.

			K.A.R.L. storm risk		
			short-term	medium-term	long-term
			2015-2044	2035-2064	2070-2099
Storm risk % <i>p.a.</i>	Reference 1985-2014	Scenario			
		SSP1-2.6	0.1297	0.1232	0.1070
	0.1163	SSP2-4.5	0.1149	0.0888	0.1064
		SSP5-8.5	0.1549	0.1362	0.1295

Table 9: Projections of the K.A.R.L. storm risk (% p.a.) for three 30-year periods and scenarios determined based on the model ensemble (CMIP6) and the selected vulnerability. The values of the reference period were derived from many worldwide observations.

General impacts The wind pressure and strong gusts resulting from storms with sustained high wind speeds can cause severe damage to infrastructure and buildings, such as blown off roofs and slapped trees or power poles. Furthermore, falling or flying objects can cause personal injuries.

2.4 Tornado (acute)

A tornado is a small-scale, but very intense storm system, whose wind speeds of sometimes more than 400 km/h are significantly higher than those of other storms, thus carrying a high potential for damage. Tornadoes are usually short-lived and have a small spatial extent with paths of normally 1 km length or less.

The analysis of the tornado risk is carried out with the natural hazard model K.A.R.L. Regional climate parameters and geographical factors are analysed for this purpose. It is assumed that wherever thunderstorms and hail are possible, tornadoes can also occur. Furthermore, it is taken into account that wide plains or only slightly hilly terrain favour the occurrence of tornadoes, while tornadoes are almost impossible in high alpine regions.

Due to the narrow path of the track, the probability of being hit by a tornado is low, so even in areas with a high tornado hazard, the calculated risks are low compared to other dangers. The calculated risk in percent per year (% p.a.) by K.A.R.L. corresponds to the expected mean annual loss. This is the loss that occurs on a long-term statistical average per year due to the natural hazard under consideration.

Current conditions The tornado risk (in relation to the year 2025) calculated by the K.A.R.L. model based on the selected vulnerability is **0.0299 % p.a.**. Consequently, there is a **low risk** for the object under investigation.

Climate outlook Table 10 lists potential future tornado risks (% p.a.), which were calculated using the K.A.R.L. model based on the selected vulnerability and an ensemble of 20 climate models for the site under investigation. The maximum projected K.A.R.L. tornado risk is **0.0304 % p.a.** and was simulated for the time period **2070-2099** and scenario **SSP5-8.5**. This results in a maximum **a low risk** in the future for the object under investigation.

			K.A.R.L. tornado risk				
			Reference	Scenario	short-term	medium-term	long-term
			1985-2014		2015-2044	2035-2064	2070-2099
Tornado risk % <i>p.a.</i>			SSP1-2.6		0.0301	0.0294	0.0286
		0.0299	SSP2-4.5		0.0295	0.0284	0.0282
			SSP5-8.5		0.0294	0.0280	0.0304

Table 10: Projections of the K.A.R.L. tornado risk (% p.a.) for three 30-year periods and scenarios determined based on the model ensemble (CMIP6). Reference period values were derived from ERA5 reanalysis data.

General impacts Although the damage of tornados is limited to a relatively narrow extent, the very high wind speeds, and wind shear (rapid change in direction or speed) pose a high risk even to massive structures. Tornadoes can destroy houses and cars, and they pose a danger to animals, people and the environment.

3 Water-related risks

3.1 Changing precipitation patterns and types (rain, hail, snow/ice) (chronic)

Changing precipitation patterns describe slow changes in accumulated precipitation or the seasonal occurrence, while extreme events are not considered.

The risk assessment is based on the average annual precipitation amounts and their adverse effects on the object under investigation(vulnerability).

Note: *No distinction is made between the different types of precipitation. In general, there will be less precipitation in frozen form due to the long-term warming of the atmosphere. However, it cannot be ruled out that in some limited regions local phenomena may also lead to more hail or snowfall. These topics are discussed in chapter 3.8.*

Current conditions In the reference period (1985-2014), the annual precipitation amount at the site is **1528.40 mm** per year. Based on the selected vulnerability, **a low adverse effect** on the object under investigation is to be expected from annual rainfall. This results in **a low risk**.

Climate outlook Table 11 lists possible future changes in annual precipitation, which were calculated based on an ensemble of 20 climate models for the site under investigation. A maximum change in annual precipitation is projected for scenario **SSP1-2.6** and time period **2035-2064** with an **increase of +35 mm** compared to the reference period.

For the maximum projected annual precipitation, **a low adverse effect** on the object under investigation is to be expected based on the selected vulnerability. This results in **a low risk**.

	Reference 1985-2014	Scenario	Projected changes compared to 1985-2014		
			short-term 2015-2044	medium-term 2035-2064	long-term 2070-2099
Annual precipitation <i>mm</i>	1528.40	SSP1-2.6	+12.10	+35.00	+27.70
		SSP2-4.5	-12.50	+7.30	+26.20
		SSP5-8.5	-2.00	-10.90	+1.90

Table 11: Projected changes in annual precipitation for the three 30-year periods and scenarios determined based on the model ensemble (CMIP6). The values of the reference period were derived from the ERA5 reanalysis data.

General impacts Changing precipitation has an impact on water management and ecosystems, as well as on agricultural and forestry production. This is also relevant for other activities related to water use, such as tourism and inland navigation.

The change in average precipitation has no direct or only a minor adverse effect on a building. The indoor climate can only be affected by persistent moisture, which can promote mold growth. Moreover, a prolonged drought can lead to a decline in groundwater and consequently to ground subsidence, which in extreme events can have a negative impact on building structures.

3.2 Precipitation or hydrology variability (chronic)

Precipitation variability describes the slow and chronic change in precipitation variability (fluctuations) that does not include individual extreme events. Strong fluctuations in precipitation influence the availability of water and water levels and can lead to extreme events such as drought (see e.g., chapters 3.6, 3.7).

The risk assessment is based on fluctuations of the annual precipitation amounts (standard deviation of the annual precipitation) and their adverse effects on the object under investigation (vulnerability). A high standard deviation of the annual precipitation indicates that very strong precipitation fluctuations occur from year to year.

Current conditions In the reference period (1985-2014), the standard deviation of the annual precipitation at the site is **240.70 mm**.

Based on the selected vulnerability, **no adverse effect** on the object under investigation is to be expected from precipitation variability. This results in **no relevant risk**.

Climate outlook Table 12 lists possible future change in precipitation variability, which were calculated based on an ensemble of 20 climate models at the site under investigation. A maximum change in precipitation variability is projected for scenario **SSP1-2.6** and time period **2070-2099** with **an increase** in precipitation variability of **+35.9 mm** compared to the reference period.

For the maximum projected change in precipitation variability, **no adverse effect** on the object under investigation is to be expected based on the selected vulnerability. This results in **no relevant risk**.

		Projected changes compared to 1985-2014			
	Reference	Scenario	short-term	medium-term	long-term
	1985-2014		2015-2044	2035-2064	2070-2099
Precipitation variability <i>mm</i>	240.70	SSP1-2.6	+16.20	+16.60	+35.90
		SSP2-4.5	+14.80	+5.70	+17.80
		SSP5-8.5	+10.40	+12.90	+30.20

Table 12: Projected changes in precipitation variability (standard deviation of the annual precipitation) for three 30- year periods and scenarios determined based on the model ensemble (CMIP6). The values of the reference period were derived from the ERA5 reanalysis data.

General impacts The variability of precipitation mainly affects the availability of water and water levels. It impacts various water users, such as water management and ecosystems, as well as all economic sectors that rely on water (e.g., fisheries, tourism, inland navigation, manufacturing, cooling, and purification). Precipitation variability tends to have no direct impact on buildings, apart from associated acute hazards (e.g., flooding in chapter 3.9), which are addressed separately. However, the quality of life and living conditions of occupants in a building can be affected through long-term changes in water availability (see chapter 3.6).

3.3 Ocean acidification (chronic)

Ocean acidification involves the uptake of (primarily anthropogenic) carbon dioxide (CO₂) by the oceans, which leads to a chemical change in seawater. When carbon dioxide reacts with seawater, carbonic acid is formed, which lowers the pH value of the oceans, causing a gradual acidification of the ocean. The pH value is a measure of the acidity and has decreased by 0.1 since the beginning of the industrial age, i.e., seawater has become more acidic.

Current and future conditions The object under investigation is located on land and is therefore not directly affected by ocean acidification. Consequently, negative effects at the site can be **excluded** currently and in the future.

General impacts Ocean acidification has negative impacts on ecosystems and the biodiversity of the oceans. The loss of biodiversity can affect millions of people who depend on fishing, aquaculture, or natural coastal protection such as coral reefs or mangroves. Ocean acidification can affect the corrosion of objects, although pH variations between 7.8 and 8.2 are not believed to cause significant changes.

3.4 Saline intrusion (chronic)

Saline intrusion is the intrusion of saltwater into coastal aquifers and surface waters. Regions with high population density are usually affected by saline intrusions due to excessive groundwater extraction.

The present analysis considers sites located at a maximum distance of 150 km from the coast. The risk assessment is based on a potential for saline intrusion and its adverse effects on the study object (vulnerability). The potential is calculated from the population density and the distance to the coast. For example, the closer a site is located to the coast and the higher the population density, the higher is the probability (or potential) that a saline intrusion may occur.

Current conditions In the reference period (1985-2014), the potential for saline intrusion is classified as **high**.

Based on the selected vulnerability, **a low adverse effect** on the object under investigation is to be expected. This results in **a low risk**.

Climate outlook Table 13 lists possible future saline intrusion potentials. The maximum potential for saline intrusion is classified as **high**.

For the maximum projected saline intrusion potential, **a low adverse effect** on the object under investigation is to be expected based on the selected vulnerability. This results in **a low risk**.

		Projected saline intrusion potential			
	Reference 1995-2014	Scenario	short-term 2021-2040	medium-term 2041-2060	long-term 2081-2100
Potential for saline intrusion	high	SSP1-2.6	high	high	high
		SSP2-4.5	high	high	high
		SSP5-8.5	high	high	high

Table 13: Hazard classification for saline intrusion. The future values are based on scenarios regarding the development of population density from the IPCC.

General impacts Saline intrusion poses a major threat to the drinking water supply of coastal areas. About 40 % of the world's population lives within 100 km of the coast. More than 100 countries and coastal regions around the world are currently affected by saline intrusion. Especially drinking water management and production in agriculture and forestry are affected by saline intrusion. The impact on ecosystems can also influence the tourism industry. Moreover, intruding salt can cause damage to buildings because of corrosion.

3.5 Sea level rise (chronic)

As a result of global warming, the sea levels around the world have risen, currently about 20 cm (global average) compared to pre-industrial times. The main causes of sea level rise are the thermal expansion of the oceans and the melting of ice and glaciers. This process will continue in the future, especially if global warming continues.

The projected sea level rises are used to identify if the object under investigation could be affected by the sea level rise. For this, sea level rise data are compared with the site's altitude and distance from the coast. The risk assessment considers the susceptibility of the object under investigation (vulnerability).

Current conditions The site is located approximately **3025,0 m** from the coast. Since the reference period (1995-2014), a current rise in the sea level (in relation to the year 2025) of **0.07 m** can be observed in the vicinity of the site.

Based on the site's elevation of **462,00 m a.s.l.** and the selected vulnerability, **no adverse effect** on the object under investigation is to be expected. This results in **no relevant risk**.

Note: *It is assumed that there is no significant protection against storm surges.*

Climate outlook Table 14 lists possible future sea level rises, which were calculated based on an ensemble of 20 climate models at the site under investigation. The maximum sea level rise of **0.64 m** is projected for scenario **SSP5-8.5** and time period **2070-2099** compared to the reference period (1995-2014).

For the maximum sea level rise, in combination with the elevation of the site and taking into account the chosen vulnerability, **no adverse effect** on the object under investigation is to be expected. This results in **no relevant risk**.

Note: *It is assumed that there is no significant protection against storm surges.*

		Projected sea level rise			
	Reference	Scenario	short-term	medium-term	long-term
	1995-2014		2021-2040	2041-2060	2081-2100
Sea level rise <i>m</i>		SSP1-2.6	0.09	0.18	0.38
	0.07	SSP2-4.5	0.09	0.20	0.48
		SSP5-8.5	0.09	0.23	0.64

Table 14: Projected sea level rise (m) for three 30- year periods and scenarios determined based on the model ensemble (CMIP6). The values of the reference period were derived from the ERA5 reanalysis data.

General impacts Sea level rise can lead to permanent flooding, making coastal areas uninhabitable. It can also cause coastal flooding, coastal erosion, and the intrusion of saltwater into ground-water reservoirs and agricultural soils. These effects can result in unusable agricultural land and drinking water reservoirs but also damage infrastructure, industries, and buildings.

3.6 Water stress (chronic)

Water scarcity or water stress refers to the chronic situation in which there is a shortage of water of sufficient quality required for humans and the environment. The risk assessment is based on the annual water availability at the site and its adverse effects on the object under investigation (vulnerability). The water availability is calculated from the difference between the annual precipitation and the effective evaporation (evapotranspiration). In theory, this amount of water can be used as surface water, or it supplements the groundwater supply through infiltration. If an annual **threshold of 200 mm** per year is exceeded, a long-term water shortage is not to be expected. The human influence on water availability, e.g., through intensive extraction of groundwater for industrial and agricultural purposes, is not considered here.

The water availability values analyzed here are calculated using the K.A.R.L. natural hazard model.

Current conditions The site under investigation is located in an area with a current water availability of **279.0 mm per year**.

Based on the selected vulnerability, **no adverse effect** on the object under investigation is to be expected. This results in **no relevant risk**.

Climate outlook Table 15 lists possible future water availability, which were calculated with K.A.R.L. based on the selected vulnerability and an ensemble of 20 climate models for the site under investigation. A maximum water stress is projected for scenario **SSP5-8.5** and time period **2070-2099** with **186.0 mm per year** at the site.

For the minimum projected water availability, **no adverse effect** on the object under investigation is to be expected based on the selected vulnerability. This results in **no relevant risk**.

		Projected water availability			
	Reference	Scenario	short-term	medium-term	long-term
	2025		2015-2044	2035-2064	2070-2099
Water availability <i>mm/year</i>		SSP1-2.6	293.0	285.0	283.0
	279.0	SSP2-4.5	278.0	272.0	248.0
		SSP5-8.5	272.0	243.0	186.0

Table 15: Projected water availability for three 30-year periods and scenarios were calculated using K.A.R.L..

General impacts Water stress has various consequences for the society such as contaminated drinking water, parched fields and an associated enhanced risk of a food crises, the spread of diseases, flight, or political and social conflicts. In addition, water shortages have ecological consequences, such as an increase in extreme droughts, declining groundwater levels and the drying up of rivers and lakes, which in turn can have a negative impact on businesses and industries.

Water stress does not have a direct adverse impact on real estate, but long-term groundwater depletion can cause subsidence, which can negatively impact the structure of a building.

3.7 Drought (acute)

Drought defines an exceptional period of water shortage due to low rainfall, high temperatures, and/or wind. The drought stress is analyzed in the present analysis using a drought stress index defined by the KA. This index includes precipitation-related parameters such as the annual precipitation, the duration of a drought, and the mean annual maximum temperature. The index values range from 0 to 10, with 0 representing no stress and 10 representing extreme and frequently recurring stress.

Current conditions With a current drought stress of **2.60**, the site under investigation is located in an area with **a low stress**.

Based on the selected vulnerability, **no adverse effect** by drought on the object of investigation is to be expected. This results in **no relevant risk**.

Climate outlook Table 16 lists possible future drought stress indices, which were calculated based on an ensemble of 20 climate models for the site under investigation. A maximum drought stress of **3.1** is projected for scenario **SSP5-8.5** and time period **2070-2099**. This corresponds to **a medium stress**.

For the maximum projected drought stress, **a low adverse effect** on the study object is to be expected based on the selected vulnerability. This results in **a low risk**.

		Projected drought stress indices			
	Reference	Scenario	short-term	medium-term	long-term
	1985-2014		2015-2044	2035-2064	2070-2099
Drought stress	2.60	SSP1-2.6	2.60	2.60	2.60
		SSP2-4.5	2.60	2.60	2.80
		SSP5-8.5	2.70	2.80	3.10

Table 16: Projected drought stress indices for three 30-year periods and scenarios determined based on the model ensemble (CMIP6). The values represent sums from the values of reference period (ERA5) and the mean anomalies of the model ensemble. The values of the reference period were derived from the ERA5 reanalysis data.

General impacts Droughts have a significant impact on agriculture causing crop failures and increased incidence of plant diseases. They endanger the life and health of humans and cause property damage and business interruptions. Industrial sectors, such as shipping or the energy industry, are also affected when river water levels drop, or power plants have to be shut down due to a lack of river water cooling. The risk of wild- and bushfires may also be exacerbated.

3.8 Heavy precipitation (rain, hail, snow/ice) (acute)

Precipitation is water from the atmosphere that reaches the earth's surface in liquid or solid form. Rain, hail, and snow are three types of precipitation that pose a substantial hazard if they occur as extreme events. A risk analysis is carried out for each of these three types of precipitation.

3.8.1 Rain

Heavy rain is defined as heavy, cloudburst-like rainfall in which very high amounts of precipitation fall in a short period of time. In contrast to continuous rain, heavy rain is a more localized phenomenon in which the amount of precipitation exceeds the seasonal average for the locality. Heavy rain often occurs during the summer season in conjunction with thunderstorms.

The natural hazard model K.A.R.L. is used to calculate the risk of heavy rain. The impact of heavy rain depends to a large extent on the absorption capacity of the local sewage systems. These sewage systems are normally designed for a 3 to 10-year rainfall event (design rainfall). If the design rainfall is exceeded, overflow and leakage of sewer water at the ground surface will occur which can cause consequential damage. For the risk assessment of K.A.R.L. it is decisive by how much the design rainfall is exceeded and with which return periods.

The calculated risk in percent per year (% p.a.) by K.A.R.L. corresponds to the expected mean annual loss. This is the loss that occurs on a long-term statistical average per year due to the natural hazard under consideration.

Current conditions The risk of heavy rainfall (based on the year 2025) calculated by K.A.R.L. based on the selected vulnerability is **0.1197 % p.a.**. This results in **a medium risk**.

Climate outlook Table 17 lists potential future heavy rain risks (% p.a.), which were calculated using the K.A.R.L. model based on the selected vulnerability and an ensemble of 20 climate models for the site under investigation. The maximum projected K.A.R.L. heavy rain risk is **0.1615 % p.a.** and was simulated for scenario **SSP5-8.5** and time period **2070-2099**. This results in **a medium risk**.

	K.A.R.L. heavy rain risk				
	Reference	Scenario	short-term	medium-term	long-term
	1985-2014		2015-2044	2035-2064	2070-2099
Heavy rain risk % p.a.		SSP1-2.6	0.1205	0.1287	0.1269
	0.1197	SSP2-4.5	0.1179	0.1314	0.1408
		SSP5-8.5	0.1228	0.1343	0.1615

Table 17: Projections of the K.A.R.L. heavy rain risk (% p.a.) for three 30-year periods and scenarios determined based on the model ensemble (CMIP6). The values of the reference period were derived from the ERA5 reanalysis data.

General impacts Heavy rain can trigger flash flooding, which can cause flooding in areas at a distance to the location where the heavy rainfall event occurs. Flooding can be also triggered by backwater from the sewage system, which can impact the infrastructure. The intrusion of water can damage buildings, vehicles and means of transport, while the ingress of water can occur in basements and underground garages.

3.8.2 Hail

Hail is frozen precipitation with a diameter of at least 0.5 centimeters. Hail is observed mainly in the summer months and in the mid-latitudes. First hail damage usually occurs from a hailstone size of 1.5 cm (e.g., damage to plants, varnish damage to cars).

The risk is assessed by the hail model integrated in K.A.R.L.. The model is based on the calculation of a worldwide hail potential, which incorporates various regional climate parameters (e.g., temperature, height of the zero-degree line, lightning frequency), which either favor or prevent the occurrence of hail.

The calculated risk in percent per year (% p.a.) by K.A.R.L. corresponds to the expected mean annual loss. This is the loss that occurs on a long-term statistical average per year due to the natural hazard under consideration.

Current conditions The hail risk (based on the year 2025) calculated by K.A.R.L. based on the selected vulnerability is **0.0085 % p.a.** This results in **a low risk** for the object under investigation.

Climate outlook Table 18 lists potential future hail risks (% p.a.), which were calculated using the K.A.R.L. model based on the selected vulnerability and an ensemble of 20 climate models for the site under investigation. The maximum projected K.A.R.L. hail risk is **0.0087 % p.a.** and was simulated for scenario **SSP5-8.5** and time period **2070-2099**. This results in **a low risk** for the object under investigation.

			K.A.R.L. hail risk				
			Reference	Scenario	short-term	medium-term	long-term
			1985-2014		2015-2044	2035-2064	2070-2099
Hail risk % <i>p.a.</i>			SSP1-2.6		0.0086	0.0083	0.0079
		0.0085	SSP2-4.5		0.0083	0.0079	0.0077
			SSP5-8.5		0.0083	0.0077	0.0087

Table 18: Projections of the K.A.R.L. hail risk (% p.a.) for three 30-year periods and scenarios determined based on the model ensemble (CMIP6). The values of the reference period were derived from the ERA5 reanalysis data.

General impacts The possible damage caused by hail varies in severity and mostly depends on the size of hailstones. Even small hailstones can cause considerable damage to plants and other susceptible objects. Larger hailstones often lead to damage to vehicles, solar systems or even buildings. Drainage systems on roofs or in streets can become clogged by hail, causing backwater and localized flooding.

3.8.3 Snow

Heavy snowfalls are events in which large amounts of snow fall in a short period of time. Regions that experience more heavy snowfalls are less prone to damage for the same amounts and times of snow.

The structural design of a building should consider the maximum possible snow load that can accumulate on the roof. This snow load differs depending on the region and altitude of the site (climato-logical factors) and the design of the building (especially the roof).

The snow loads used in the present analysis, are calculated with the natural hazard model K.A.R.L. based on globally available climate data. The modeling approach was calibrated against numerous specific local recommendations and building regulations from different climatic zones and topographic elevations worldwide. The risk calculation does not take into account the design of a building.

Note: *The snow loads given here are values that relate to an extremely rare event (> return period 100). From a risk management perspective, these values are interesting, but they are not suitable as a basis for the structural design of buildings. For this purpose, please use the official standard values. These standardized snow loads are usually much lower than the values given in the present study.*

Current conditions The snow load for the current conditions is **0.0 kg/m²**.

Based on the selected vulnerability, **no risk** due to snow load is to be expected.

Climate outlook Table 19 lists possible future snow loads calculated with K.A.R.L. considering the selected vulnerability and based on an ensemble of 20 climate models for the site under investigation. A maximum snow load at the site is projected for scenario **SSP1-2.6** and time period **2015-2044** and is **0.0 kg/sqm**.

For the projected maximum snow load, **no adverse effect** on the object under investigation is to be expected based on the selected vulnerability. This results in **no relevant risk**.

		K.A.R.L. snow load			
	Reference	Scenario	short-term	medium-term	long-term
	1985-2014		2015-2044	2035-2064	2070-2099
Snow load <i>kg/m²</i>		SSP1-2.6	0.0	0.0	0.0
	0.0	SSP2-4.5	0.0	0.0	0.0
		SSP5-8.5	0.0	0.0	0.0

Table 19: Projections of the K.A.R.L. snow loads (kg/m²) for three 30-year periods and scenarios determined based on the model ensemble (CMIP6). The values of the reference period were derived from the ERA5 reanalysis data.

General impacts Heavy snowfalls result in large amounts of snow in a short time, which can cause significant damage. The weight of the snow not only damages trees, power lines and buildings, but also impairs the usability of transport infrastructures (road, rail, air), which can lead to supply bottlenecks. Furthermore, large amounts of snow and ice can also be significant for agriculture and forestry as well as for the tourism and event industry.

3.9 Flood (coastal, fluvial, pluvial, groundwater) (acute)

In the present analysis, floods are divided into coastal floods, i.e., storm surges, and general floods. The latter refers to floods that are exclusively caused by a temporary excess of water. It can be caused by river floods (fluvial), but also by heavy rainfall events (pluvial). Groundwater flooding (flooding or infiltration of water by groundwater) is not considered in this analysis.

3.9.1 Coastal flooding (storm surge)

A storm surge is an unusual high rise of water along the coasts and in tidal rivers that exceeds the normal tidal range. High-water levels occur especially when a storm surge occurs during a spring tide. Storm surges occur when strong winds (storms and hurricanes) across the ocean push water towards the shore and pile it up.

Current and future conditions Due to the local elevation of more than 10 meters above sea level, storm surges can be ruled out by human estimation, despite a distance to the coast of only approximately **3025,0 m**. This results in **no relevant risk** from storm surge.

General impacts Storm surges can cause extreme flooding in coastal areas and hence damage buildings, infrastructure, or protective measures (e.g., levees). Storm surges can cause property damage to boats and ships in harbors and contribute to beach erosion. In estuaries and bays, seawater can penetrate inland during a storm surges resulting in the salinization of groundwater reservoirs, which can have negative consequences for the water supply.

3.9.2 River flood

River flood is the rise in the water level of rivers or streams caused by heavy precipitation, often also associated with snow melt. Flooding of major river systems often results from extensive and long-lasting heavy precipitation in the upper river basin that leads to flooding. In smaller river systems, local heavy precipitation is often sufficient to cause localized flooding.

The risk of river floods (also referred to as inundation) is assessed using the flood model integrated in K.A.R.L.. The flood model first determines the flood hazard (e.g., is the site in a depression or does it have good drainage?) of the site by examining the terrain profile (elevation model) of the site and its surrounding. Consequently, climatological, hydrological, and geographic factors are used to estimate water levels and return periods.

Current conditions The location under survey is in a hilly or mountainous area with significant peaks and valleys. Here extreme precipitation can lead to flash floods or mud flows with a high potential of destruction. Such occurrences are very rare - however, should they happen the endangerment is especially high if the location under survey is situated in a valley bottom or on the lower part of a slope.

The flood risk (based on the year 2025) calculated by K.A.R.L. based on the selected vulnerability is **0.0000 % p.a.**. This results in **no relevant risk**.

Climate outlook Table 20 lists potential future flood risks (% p.a.), which were calculated using the K.A.R.L. model based on the selected vulnerability and an ensemble of 20 climate models for the site under investigation.

Assuming no change in geography at the site, the maximum projected K.A.R.L. flood risk is **0.0000% p.a.** and was simulated for scenario **SSP1-2.6** and time period **2015-2044**. This results in **no relevant risk**.

		K.A.R.L. flood risk			
	Reference	Scenario	short-term	medium-term	long-term
	1985-2014		2015-2044	2035-2064	2070-2099
Flood risk % p.a.		SSP1-2.6	0.0000	0.0000	0.0000
	0.0000	SSP2-4.5	0.0000	0.0000	0.0000
		SSP5-8.5	0.0000	0.0000	0.0000

Table 20: Projections of the K.A.R.L. flood risk (% p.a.) for three 30-year periods and scenarios determined based on the model ensemble (CMIP6). The values of the reference period were derived from the ERA5 reanalysis data.

General impacts River floods can inundate areas close to rivers and cause damage to infrastructure, buildings, vehicles, and agricultural land, among other things. Flooding, e.g., in urban areas, can release pollutants that contaminate water bodies, groundwater and soils.

3.10 Glacial lake outburst (acute)

Glacial lake outbursts are floods caused by the release or overflow of glacial lakes. Glacial lakes are naturally occurring lakes dammed by ice and moraines that are located within, on top of, or at the edge of glaciers. Glacial lake outburst occurs either when the lake overflows or when damage occurs to the dam. Due to the global increase in temperature and the melting of glaciers, a more frequent occurrence is expected temporarily in areas where glaciers are still present.

Current and future conditions There is **no** known current glacier within a radius of 30 km around the site under investigation. Consequently, negative effects from glacial lake outburst at the site can be **excluded** currently and in the future.

General impacts When glacial lakes fail, enormous amounts of water and debris are released within a very short time. These floods can be catastrophic with serious consequences for any life in the valley below. Therefore, glacial lake outbursts can cause a high number of fatalities. Although predicted widespread deglaciation may stop most outbreaks in the long term, global warming will contribute to earlier and more frequent glacial lakes outburst in the short term. In total, about 15 million people worldwide are now at risk from these floods.

4 Soil-mass-related risks

4.1 Coastal erosion (chronic)

Coastal erosion is the gradual change of the coast by tides and weather influences (e.g., wind, precipitation). Natural events such as hurricanes, earthquakes, storm surges and tsunamis, just as human actions (e.g., construction of a dam) contribute to coastal erosion. In addition, ports and infrastructures can obstruct the natural transport path of sand, making the coastal zone vulnerable to erosion. Besides the direct damage to the building, coastal erosion can also have indirect effects, such as damage to the surrounding infrastructure.

Due to data availability, only erosion of sandy coasts is considered in the present analysis. Although erosion can alter any type of shoreline, the effects are greatest for soft material (e.g., sand, silt, clay).

Note: *The projected erosion value can be both positive and negative. Positive values indicate accretion of the coast, increasing the distance from the coast. Negative values indicate a reduction of the coastline, thereby decreasing the distance to the site the distance to the location. Consequently, the highest negative erosion value is decisive for the risk at the site, as it results in the shortest distance to the coast. 'NoData' values does not necessarily indicate missing data or a relevant hazard. They occur, for example, near cliffs or coastal cities, where the risk of coastal erosion is generally limited because it can be assumed that the coasts are protected and stabilised by appropriate protective measures.*

Current and future conditions The distance to the coast is **more than 2 km**. Therefore, negative effects from coastal erosion at the site under investigation can be **excluded** currently and in the future.

General impacts Coastal erosion can reduce habitual human space and destroy infrastructure or commercially used land. As a result of coastal erosion and the landward retreat of the shoreline, salt water can penetrate the groundwater reservoir and cause salinization. Tourism is also negatively affected by coastal erosion, as e.g., beaches can no longer be used accordingly. In addition, the natural habitats of flora and fauna in the coastal land and in the sea change as erosion progresses, which can result in the loss of biodiversity.

4.2 Soil erosion (chronic) and soil degradation (chronic)

Soil degradation describes the degradation of soils up to irreversible destruction, for example through nutrient loss, acidification, or decalcification. Soil erosion is the most problematic and widespread form of soil degradation. Soil functions such as soil fertility or storage capacity can decrease due to erosion until the entire soil substance is destroyed. Soil erosion is mostly caused by water, with heavy rainfall being the main cause. Human actions, such as deforestation, urbanization, agricultural tillage, and fertilization, can also contribute to soil erosion and degradation.

Current conditions At the site under investigation, **a low hazard** of soil erosion or soil degradation is to be expected. Based on the selected vulnerability, this results in **no relevant risk**.

Climate outlook For the maximum projected erosion rates, **a high hazard** is to be expected for the object under investigation. Based on the selected vulnerability, this results in **a low risk**.

		Projected hazard classification				
		Reference	Scenario	short-term	medium-term	long-term
		1985-2014			2070	
Soil erosion, soil degradation			SSP1-2.6	n/A	low	n/A
	low		SSP2-4.5	n/A	medium	n/A
			SSP5-8.5	n/A	high	n/A

Table 21: Hazard classification of soil erosion. n/A = not available: No data are currently available for this period.

General impacts Soil degradation and soil erosion have severe consequences for agriculture. Soil degradation can reduce the quality of the soil to such an extent that it can no longer be used for agriculture. This can lead to food shortages for the growing world population. In addition, the soil loses its ability to store water, which results in an increasing risk of flooding. Soil erosion removes the protective vegetation cover, leaving the soil defenseless against natural processes. If the rainwater runs off, the fertile soil (top layers) as well as the nutrients that are still present are flushed out. Furthermore, the removed soil material (sediments) can be deposited on neighboring areas, roads or in bodies of water.

4.3 Solifluction (chronic)

Solifluction (earth flow, soil flow) is a slow, down-slope flow movement of water-saturated rock and soil material of the topsoil. Solifluction often occurs in the layers where permafrost thaws and additionally requires some slope of the terrain. When the surface of the permafrost thaws, water can accumulate on top of the frozen ground as it cannot percolate into the frozen ground. Consequently, this water flows downslope and transports overlying loose rock and solid material.

Since solifluction and the associated risk can only occur in the vicinity of permafrost, the present analysis examines whether a site is located in a permafrost area or in the immediate vicinity of it. Therefore, the basis of this risk assessment is analogous to the approach used to assess the risk for permafrost thawing (see 1.4).

Current and future conditions It can be **excluded** that the site under investigation is currently or will be in the future located in a permafrost region. Therefore, negative effects from solifluction at the site can be **excluded** currently and in the future.

General impacts Solifluction affects the erosion of sediments and therefore the morphology of the mountain landscape. Within or in the proximity of the area where solifluction occurs, slope stabilization measures and infrastructures, as well as hiking trails and buildings, may be at risk from flow movements.

4.4 Avalanche (acute)

An avalanche describes a mass of snow or ice that detaches from mountain slopes in alpine terrain and descends into the valley. It typically occurs on slopes with an inclination of 30 degrees or more. The deposits caused by their movement and the accompanying air pressure wave can cause significant damage. Conditions which favour an avalanche include high amounts of snow and strong winds. Avalanches are often triggered by temperature fluctuations, rockfalls, or human activities.

In the present analysis, the avalanche hazard is determined based on the slope inclination, the average temperature during the coldest winter months, and the amount of precipitation during this period. From these parameters, a dimensionless avalanche hazard index (values between 0 and 9, with high values indicating a high hazard) is calculated, which serves as the basis for risk assessment.

Note: *At average minimum temperatures of over 2.5°C during the coldest winter months, it is assumed that the occurrence of avalanches is ruled out due to the climatological conditions at the location. Furthermore, if the terrain in the vicinity of the site is too flat, an avalanche risk can also be excluded.*

Current and future conditions An average minimum temperature of **16,50°C** during the coldest winter months is assumed at the site under investigation under current climatic conditions. Therefore, the occurrence of avalanches due to the climatological conditions at the site is almost impossible, which results in a **no relevant risk**. Due to global warming, there will also not be a risk of avalanches at the site in the future.

General impacts The hazard associated to avalanches is governed by the enormous masses of snow and other objects carried along (e.g., trees and stones) but also by the enormous pressure wave generated by the avalanche. If a building is hit, the resulting effects vary depending on the strength of the pressure, ranging from deformed and cracked walls to a destroyed roof or even in the complete destruction. Avalanches can also affect tourist activities as well as infrastructure.

Climate change will significantly affect the seasonal snow cover in mountain regions, probably leading to a decrease in the overall frequency of avalanches. The reduction in snow cover at lower elevations will decrease the area where avalanches can occur.

4.5 Landslide (acute)

A landslide refers to the downslope movement of material, which can fall, tumble, slide, flow, and spread, depending on the underpinning geological conditions. The triggers for such movements are various, while precipitation and earthquakes play a major role. Human activities can also trigger landslides.

The landslide susceptibility classification of the site used for the present analysis is based on a Global Facility for Disaster Reduction and Recovery (GFDRR) data set from 2021, which incorporates precipitation and earthquakes as driving forces behind landslides. The site does not necessarily have to be located in the area of the landslide itself but may be damaged by incoming material.

Current conditions At the site under investigation, **a medium hazard** of landslides is to be expected. Based on the selected vulnerability, this results in **a low risk**.

Climate outlook Table 22 lists the possible future hazard classification for landslides. Both increasing heavy rain events and large amounts of precipitation over a long period of time can increase the hazard of landslides. Our developed precipitation stress index combines these factors. It is assumed, that an increase in the precipitation stress index also increases the hazard of landslides. For the maximum projected hazard the future, **a high hazard** of landslides on the object under investigation is to be expected. Based on the selected vulnerability, this results in **a medium risk**.

			Projected hazard classification			
		Reference	Scenario	short-term	medium-term	long-term
		1985-2014		2015-2044	2035-2064	2070-2099
Landslide			SSP1-2.6	medium	medium	medium
		medium	SSP2-4.5	medium	medium	medium
			SSP5-8.5	medium	medium	high

Table 22: Hazard classification of landslides.

General impacts Landslides can have serious consequences. They can swallow houses and roads, and transport large amounts of debris into the valley damaging people, ecosystems, and infrastructure. Increasing urbanization and climate change are expected to further increase the risk from landslides. It is not uncommon for landslides to lead to homelessness, food loss or, in the worst case, to fatalities.

4.6 Subsidence (acute)

Ground subsidence, or subsidence, is the lowering of the soil. This can be caused by natural geological processes, such as erosion or earthquakes, whereas human actions dominate. Groundwater depletion (e.g., by sustained groundwater extraction) is particularly crucial and is therefore considered in the present analysis.

The present analysis is based on a data set that describes the probability of subsidence for the year 2010 (representing the current conditions) and the evolution for the year 2040. The data set is based on many different variables such as land use, climate, population density, and groundwater storage.

Current conditions At the site under investigation, **low hazard** of subsidence is to be expected. Based on the selected vulnerability, this results in **a low risk**.

Climate outlook Different from the other climate risk analyses, **scenario SSP2-8.5** was used for the future projection, which assumes a steady population growth as well as increasing greenhouse gas emissions. In the future, **low hazard** of subsidence at the site under investigation is to be expected based on the selected vulnerability. This results in **a low risk**.

General impacts Subsidence poses a gradual threat to people and the environment. Possible consequences of subsiding ground include water stress and an increased risk of flooding, especially in coastal areas. Furthermore, subsidence can damage buildings and infrastructure (e.g., power supply).

Preliminary references and links for further reading*

**References will be updated and verified when the automation is finalized.*

- Borrelli P., Robinson D.A., Panagos P., Lugato E., Yang J.E., Alewell C., Wuepper D., Montanarella L., Ballabio C. 2020. Land use and climate change impacts on global soil erosion by water (2015-2070). Proceedings of the National Academy of Sciences (PNAS), 117(36), 21994–22001; DOI: 10.1073/pnas.2001403117
- Buchhorn, M. ; Smets, B. ; Bertels, L. ; De Roo, B. ; Lesiv, M. ; Tsendbazar, N. - E.; Herold, M. ; Fritz, S. Copernicus Global Land Service: Land Cover 100m: collection 3: epoch 2019: Globe 2020
- Center for International Earth Science Information Network - CIESIN - Columbia University. 2018. Gridded Population of the World, Version 4 (GPWv4): Population Density, Revision 11. Palisades, New York: NASA Socioeconomic Data and Applications Center (SEDAC)
- Chadburn, Sarah et al. (2017): An observation-based constraint on permafrost loss as a function of global warming. Nature Climate Change
- Chadburn, Sarah; Burke, Eleanor J; Cox, Peter; Friedlingstein, Pierre; Hugelius, Gustaf; Westernmann, Sebastian (2017): Estimated future permafrost maps constrained by observed relationships, with link to model result files in NetCDF format. PANGAEA
- Deutsches Klimarechenzentrum. Klimamodelldaten CMIP6 (as of 2021)
- European Commission, Joint Research Centre (JRC) (2019): Global shoreline change projections. European Commission, Joint Research Centre (JRC) [Dataset] DOI: 10.2905/18EB5F19-B916-454F-B2F5-88881931587E PID
- GLIMS Consortium. 2005. GLIMS Glacier Database, Version 1. Boulder, Colorado USA. NASA National Snow and Ice Data Center Distributed Active Archive Center.
- Global Facility for Disaster Reduction and Recovery (GFDRR), 2020: Global Landslide Hazard Map
- Gutiérrez, J.M., R.G. Jones, G.T. Narisma, L.M. Alves, M. Amjad, I.V. Gorodetskaya, M. Grose, N.A.B. Klutse, S. Krakovska, J. Li, D. Martínez-Castro, L.O. Mearns, S.H. Mernild, T. Ngo-Duc, B. van den Hurk, and J.-H. Yoon, 2021: Atlas. In Climate Change 2021: The Physical Science Basis. Contribution of Working Group I to the Sixth Assessment Report of the Intergovernmental Panel on Climate Change [Masson-Delmotte, V., P. Zhai, A. Pirani, S.L. Connors, C. Péan, S. Berger, N. Caud, Y. Chen, L. Goldfarb, M.I. Gomis, M. Huang, K. Leitzell, E. Lonnoy, J.B.R. Matthews, T.K. Maycock, T. Waterfield, O. Yelekçi, R. Yu, and B. Zhou (eds.)]. Cambridge University Press.
- Herrera-García, G., Ezquerro, P., Tomás, R., Béjar-Pizarro, M., López-Vinielles, J., Rossi, M., et al. (2021). Mapping the global threat of land subsidence. Science, 371(6524), 34–36
- Iturbide, M., Fernández, J., Gutiérrez, J.M., Bedia, J., Cimadevilla, E., Díez-Sierra, J., Manzananas, R., Casanueva, A., Baño-Medina, J., Milovac, J., Herrera, S., Cofiño, A.S., San Martín, D., García-Díez, M., Hauser, M., Huard, D., Yelekçi, Ö. (2021) Repository supporting the implementation of FAIR principles in the IPCC-WG1 Atlas. Zenodo, DOI: 10.5281/zenodo.3691645.
- Knapp, K. R., M. C. Kruk, D. H. Levinson, H. J. Diamond, and C. J. Neumann, 2010: The International Best Track Archive for Climate Stewardship (IBTrACS): Unifying tropical cyclone best track data. Bulletin of the American Meteorological Society, 91, 363-376. DOI: 10.1175/2009BAMS2755.1
- Knapp, K. R., H. J. Diamond, J. P. Kossin, M. C. Kruk, C. J. Schreck, 2018: International Best Track Archive for Climate Stewardship (IBTrACS) Project, Version 4. [indicate subset used].

NOAA National Centers for Environmental Information. DOI: 10.25921/82ty-9e16

- Kaplan, J. O. und Lau, K. H.-K., 2021. The WGLC global gridded lightning climatology and time series. Earth System Science Data, 13, 3219–3237.
- OpenStreetMap:
<http://www.openstreetmap.org/copyright>
- Vousdoukas, M., Ranasinghe, R., Mentaschi, L., Plomaritis, T., Athanasiou, P., Luijendijk, A. and Feyen, L., Sandy coastlines under threat of erosion, NATURE CLIMATE CHANGE, ISSN 1758-678X (online), 10, 2019, p. 260-263, JRC117344.: DOI 10.1038/s41558-020-0697-0

Disclaimer

The K.A.R.L.[®]-Taxo-report is created by the KA Köln.Assekuranz Agentur GmbH (KA).

The contents of this report and the data used correspond to the available current state of knowledge. All data has been carefully prepared and checked by KA. On this basis, the report is created automatically and made available without further manual checking.

To the fullest extent permitted by law, KA makes no warranties of any kind, express or implied, either on its own behalf or on behalf of any of its providers, licensors, employees and agents. This applies in particular with respect to the report, or the results obtained using the report, including but not limited to

1. all warranties as to the accuracy, completeness, timeliness, or non-infringement of the Reports, and
2. any warranties of reasonable care, merchantability, or fitness for a particular purpose.

The responsibility for the use and interpretation of the climate risk analysis data lies solely with you.

IMPORTANT NOTE: This report was created automatically and therefore not checked for plausibility by a scientific expert. The values given are not predictions, but possible developments that correspond to the emission scenarios.

Imprint

KA Köln.Assekuranz Agentur GmbH
Scheidtweilerstr. 4
50933 Cologne
Tel.: +49 221 39761-200
Fax: +49 221 39761-301
info@koeln-assekuranz.com
www.koeln-assekuranz.com

© 2025 KA Köln.Assekuranz Agentur GmbH